



THE 815 SERIES FITTING ARE STRAIGHT THREAD O-RING SEAL DESIGN. THE THREAD IS THE SAME ON BOTH ENDS OF THE FITTING. THE FLARE ANGLE IS 37 DEGREES. ALL FITTINGS INCLUDE THE O-RING. THE O-RING COMPUND IS BUNA N, WHICH IS COMPATIBLE WITH GASOLINE AND ALCOHOL. O-RINGS ARE AVAILABLE FOR NITROMETHANE. ALL ALUMINUM FITTINGS ARE SULPHURIC ANODIZED AND DYED BLACK, THE O-RING SIDE OF THE FITTING HAS A CONTOURED, HI-FLOW ENTRY.

PLEASE SEE 919 SERIES FOR FITTINGS WITH DIFFERENT THREAD SIZE ON EITHER END.

	A (THRD)	B(HOLE)	C(LENGTH)	D(LENGTH)	E (LENGTH)	F(HEX)
*815-3	3/8-24	.150	.419	.300	.945	7/16"
815-3A	3/8-24	.150	.419	.300	.945	7/16"
815-6	9/16-18	.300	.550	.300	1.085	11/16"
*815-6B	9/16-18	.300	.550	.300	1.163	11/16"
815-8	3/4-16	.390	.660	.390	1.300	7/8"
815-8L	3/4-16	.390	.660	.390	2.206	7/8"
815-10	7/8-14	.484	.758	.385	1.393	1"
815-10L	7/8-14	.484	.758	.385	2.200	1"
815-12	1 1/16-12	.610	.864	.400	1.582	1 1/4"
815-16	1 5/16-12	.845	.911	.400	1.667	1 5/8"
815-20	1 5/8-12	1.080	.958	.500	1.808	1 7/8"

* BRASS

